Industry-leading output of 100 ppm in colour and B&W

Long-running reliability, 1,000,000-page monthly duty cycle

Enhanced Simitri™ HD^E toner for superior halftone and skin-tone reproduction

Image quality that rivals offset printing at a fraction of the cost

Optimized 1200 x 1200 dpi resolution with 8-bit processing

SEAD IV screen processing to continuously maintain image stability over long press runs

Hybrid decurling function for higher productivity

Increased paper handling with 13,890-sheet capacity and weights from 55 to 350 gsm

Air suction paper handling that ensures virtually jam-free printing

200-page face-trimmed saddle-stitched booklet option

600-page perfect-bound books with post-fusing cover insertion

15" Colour LCD touch-panel – can be placed anywhere on unit

Fiery®, Creo® and Konica Minolta image controller options

bizhub PRESS C1100

FULL COLOUR DIGITAL PRODUCTION PRINTER

press

press

bizhub PRESS C1100
FULL COLOUR DIGITAL PRODUCTION PRINTER

Description

bizhub PRESS C1100 Overview	The high-speed bizhub® PRESS C1100 sets a new standard in digital productivity, producing 5,000 or more sides per hour – saving space on your production floor and reducing time and labour costs by incorporating powerful inline finishing options, simple setup and familiar PC-like operation with hand-held mouse.

System Specifications

Resolution	1,200 x 1,200 dpi x 8 bit
	1,200 x 3,600 dpi equivalent
Paper weight	55-350 gsm
Duplex unit	Non-stack type; 55-350 gsm
Paper sizes	Up to 330 x 487 mm (13" x 19.2")
Maximum image area	321 x 480 mm
Paper input capacity	Max.: 13,890 sheets
Paper output capacity	Max.: 13,600 sheets
Main unit dimensions	35.5" x 37.5" x 52" (W x D x H)
Main unit weight	948 lb

Productivity

8.5" x 11"	Max. per minute: 100 ppm
11" x 17"	Max. per minute: 53 ppm
12" x 18"	Max. per minute: 50 ppm
8.5" x 11"	Max. per hour: 5,192 pph
11" x 17"	Max. per hour: 2,762 pph
12" x 18"	Max. per hour: 2,581 pph

Controller

IC-308	External EFI Fiery Controller
IC-310	External EFI Fiery Controller
IC-312*	External Creo Controller
IC-602	Internal Konica Minolta Controller

Scanner Specifications

Scan speed A4	Up to 42 opm
Scan resolution	600 x 600 dpi
Scan modes	TWAIN scan; Scan-to-HDD; Scan-to-FTP; Scan-to-SMB; Scan-to-email
Scan formats	TIFF (single and multi-page); PDF

Copier Specifications

Gradations	256
Magnification	25-400%, in 0.1% steps
Multiple copies	1-9,999

Options

HM-101	Humidification unit for RU-511
HT-506	Heating unit for PF-707/8
FD-503	Folding and punching unit
FS-532	100-sheet Stapling unit
GP-501	Multi (GBC) punching unit
GP-502	Auto ring binding unit
LS-506	Stacking unit
PB-503	Perfect binding unit
PF-707	Air suction paper feed unit
PF-708	Air suction paper feed unit with ADF
PI-502	Post inserter for FS-532
PK-522	Punch kit for FS-532
RU-510	Reversing Relay unit
RU-511	Decurling Relay unit
SD-506	Saddle-stitch unit
SD-510	Saddle-stitch unit for FS-532
WT-512	Working Table

* Not available at time of launch.

In Support of
Canadian
Breast Cancer
Foundation

Item #: C1100SS
6/14